



ZINGALU

EASY CORROSION PROTECTION WITH METALLIC FINISH

ZINGALU IS A ONE COMPONENT FILM GALVANISING SYSTEM

ZINGALU is a one component film galvanising system for active cathodic protection. ZINGALU contains 90% zinc and 4% aluminium flakes in the dry film which provides long lasting corrosion protection. The aluminium flakes offer barrier protection and a bright colour, resembling the finish of galvanised surfaces. ZINGALU is ideal as a stand-alone system as well as for repairing and touching up of damaged or old hot-dipped, Zingalised or other zinc coated structures.



AESTHETIC FINISH

- Comparable to Hot Dip Galvanisation
- Long lasting metallic finish

CATHODIC PROTECTION

- Excellent anti-corrosion performance
- Passed 6.000 hrs salt spray
- Added barrier protection

EASY APPLICATION

- One component coating
- By brush, roller, conventional or airless spray
- Easily reloaded for future maintenance





COMPARISON WITH METALLISATION *



ZINGALU



METALLISATION

*2.000 hrs salt spray

PRACTICAL INFORMATION

APPLICATION

Easy application by brush, roller, conventional or airless spray

COVERAGE AND CONSUMPTION

for 60 μm DFT: 0,23 Kg/m²
for 120 μm : 0,47 Kg/m²

RECOMMENDED SYSTEM

ZINGALU is used as stand-alone system, applied with an average thickness of DFT 80-160 μm .

FOR MORE INFORMATION

See Technical Data Sheet or ask a Zingametall representative

AFTER 150 DAYS OF EXPOSURE



ZINGAMETALL Bvba Sprl

Industriepark T. +32 9 385 68 81
Rozenstraat 4 info@zinga.be
9810 Eke (Belgium) www.zinga.eu